

CASE FILE
COPY

Stability Criteria for a Cantilever Subjected
to a Time-Dependent Follower Force

by

R. H. Plaut^{*}

Center for Dynamical Systems
Brown University
Providence, Rhode Island

*This research has been supported by the National Aeronautics and Space Administration under Contract No. NGR 40-002-015, The United States Army under Contract No. DA-31-124-ARO-D-270, and by the United States Air Force under Contract No. AFOSR-693-67

Introduction

In this Note we investigate the stability of a nonconservative nonautonomous system, a cantilevered column subjected at its free end to a compressive follower force which varies with time. Viscous damping is assumed to be present. With the use of a Liapunov type of approach, conditions are obtained which guarantee asymptotic stability or almost sure asymptotic stability of the column.

Consider a linear elastic column, built-in at one end and free at the other. In nondimensional terms, the equation of motion for the lateral displacement $w(x,t)$ is assumed to be

$$w_{,xxxx} + p(t)w_{,xx} + 2\xi w_{,t} + w_{,tt} = 0 \quad (1)$$

where $0 < x < 1$, $t \geq 0$, and a comma denotes partial differentiation. The x axis lies along the undisturbed straight column, with $x = 0$ at the built-in end and $x = 1$ at the free end. $\xi (> 0)$ is the damping coefficient. The compressive force $p(t)$ is applied at the free end and remains tangent to the column during motion. We assume $p(t)$ is continuous for $t > 0$. The boundary conditions are

$$w(0,t) = w_{,x}(0,t) = w_{,xx}(1,t) = w_{,xxx}(1,t) = 0 \quad (t \geq 0) \quad (2)$$

and the initial conditions are given by

$$w(x,0) = w_0(x), \quad w_{,t}(x,0) = v_0(x). \quad (3)$$

Stability Analysis I

It is assumed that $p(t)$ is strictly stationary and satisfies an ergodic property which insures the equality of time averages and ensemble averages. Then

$$E\{|p(t)|\} = \lim_{t \rightarrow \infty} \frac{1}{t} \int_0^t |p(\tau)| d\tau \quad (4)$$

exists with probability one [1].¹

Consider the functional

$$V(w, v) = \int_0^1 [w_{,xx}^2 + v^2 + 2\xi vw + c\xi^2 w^2] dx \quad (5)$$

where $w_{,xx}^2 = (w_{,xx})^2$, $v = w_{,t}$ and

$$c = \begin{cases} 1 & \text{if } 0 < \xi \leq \pi^2/2 \\ (8\xi^2 - \pi^4)/4\xi^2 & \text{if } \xi > \pi^2/2 \end{cases} \quad (6)$$

Note that $V = 0$ if $w = v = 0$, with $V > 0$ otherwise. The total time derivative of V along solutions of (1) and (2) can be written in the form

$$\dot{V}(w, v, t) = -2 \int_0^1 [\xi w_{,xx}^2 + \xi v^2 + (2-c)\xi^2 vw + p(t)w_{,xx}(v+\xi w)] dx \quad (7)$$

with the use of integration by parts.

For w and v not both zero consider the ratio \dot{V}/V , which

¹Numbers in brackets designate References at end of Note.

we write as

$$\dot{V}/V = -\lambda - \gamma p(t) \quad (8)$$

where

$$\lambda = \frac{2\xi}{V} \int_0^1 [w_{,xx}^2 + v^2 + (2-c)\xi vw] dx, \quad \gamma = \frac{2}{V} \int_0^1 (v + \xi w) w_{,xx} dx. \quad (9)$$

Then

$$\dot{V}/V \leq -\lambda + |\gamma| |p(t)|. \quad (10)$$

Using the calculus of variations we can show that $\lambda \geq \lambda_m$ where

$$\lambda_m = \begin{cases} 2\xi(\pi^2 - \xi\sqrt{2})/\pi^2 & \text{if } 0 < \xi \leq \pi^2/2 \\ 2\xi - [(8\xi^2 - \pi^4)/2]^{1/2} & \text{if } \xi > \pi^2/2 \end{cases} \quad (11)$$

and from the inequality

$$|\int_0^1 2(v + \xi w) w_{,xx} dx| \leq \int_0^1 [w_{,xx}^2 + (v + \xi w)^2] dx \leq V(w, v) \quad (12)$$

it follows that $|\gamma| \leq 1$. Therefore

$$\dot{V}/V \leq -\lambda_m + |p(t)|. \quad (13)$$

Integrating this expression between 0 and t yields

$$V(t) \leq V(0) \exp\{t[-\lambda_m + \frac{1}{t} \int_0^t |p(\tau)| d\tau]\} \quad (14)$$

where $V(t) = V[w(x,t), v(x,t)]$ and $V(0) = V[w_0(x), v_0(x)]$.

Now assume that

$$E\{|p(t)|\} \leq \lambda_m - \varepsilon \quad (15)$$

for some constant $\varepsilon > 0$, as small as desired. Since $V(t) \geq 0$ it then follows from (4) and (14) that, with probability one, $V(t) \rightarrow 0$ as $t \rightarrow \infty$, and therefore also $\int_0^1 w_{,xx}^2 dx \rightarrow 0$, $\int_0^1 w^2 dx \rightarrow 0$, and $\int_0^1 v^2 dx \rightarrow 0$ as $t \rightarrow \infty$. We conclude that (15) is a sufficient condition for almost sure asymptotic stability in the large [2]².

The boundary of the stability region defined by (15) is depicted by the solid line in Fig. 1.

²To be explicit we should define the stability in terms of a norm; for example, we could use the norm $\rho(w,v) = [\int_0^1 (w_{,xx}^2 + v^2) dx]^{1/2}$.

Stability Analysis II

In this section we obtain stability criteria in terms of

$$\max_{t \geq 0} |p(t)|.$$

From (13) one can show that

$$V(t) \leq V(0)e^{-\varepsilon t} \quad (16)$$

if

$$\max_{t \geq 0} |p(t)| \leq \lambda_m - \varepsilon \quad (17)$$

for some $\varepsilon > 0$. Therefore (17) is a sufficient condition for asymptotic stability of the column (see Fig. 1).

For $\xi > 4.66$ a stronger condition than (17) can be obtained by the use of a different technique. Consider the functional V as in (5), except let $c = 2(1-\delta)$ where $0 < \delta < 1/2$. We can write \dot{V} in the form

$$\dot{V}(w,v,t) = -2\xi\delta V(w,v) - 2W(w,v,t) \quad (18)$$

where

$$W(w,v,t) = \int_0^1 [\xi(1-\delta)(w_{,xx}^2 + v^2 - 2\xi^2\delta w^2) + \xi p(t)ww_{,xx} + p(t)vw_{,xx}] dx. \quad (19)$$

We now seek conditions on $p(t)$ under which $W \geq 0$.

The calculus of variations can be used to show that

$$\int_0^1 w_{,xx}^2 dx \geq \frac{\pi^4}{8} \int_0^1 w^2 dx \quad (20)$$

where w satisfies (2). We then can write

$$W \geq \int_0^1 \{ \xi(1-\delta) [(1-\alpha) w_{,xx}^2 + v^2 + (\frac{\pi^4}{8} \alpha - 2\xi^2 \delta) w^2] + \xi p(t) w w_{,xx} + p(t) v v_{,xx} \} dx \quad (21)$$

where $0 < \alpha < 1$. The integrand in (21) has the form

$$(a w_{,xx}^2 + b w_{,xx} v + c v^2) + (A w_{,xx}^2 + B w_{,xx} w + C w^2),$$

which will be non-negative if $a \geq 0$, $A \geq 0$, $b^2 \leq 4ac$, and $B^2 \leq 4AC$.

If the optimum values of α , A/a , and δ are chosen, it can be shown that these conditions are satisfied if

$$\max_{t \geq 0} |p(t)| \leq 2\xi (\sqrt{8\xi^2 + \pi^4} - 2\sqrt{2}\xi) / \pi^2 \quad (22)$$

for some $\varepsilon > 0$. It then follows that $\dot{W} \leq 0$, $\dot{V} \leq -2\xi \delta V$, and

$$0 \leq V(t) \leq V(0) e^{-2\xi \delta t} \quad (23)$$

Therefore $V(t) \rightarrow 0$ as $t \rightarrow \infty$, and we conclude that (22) is a sufficient condition for asymptotic stability in the large.

The boundary of the stability region defined by (22) is depicted by the dashed line in Fig. 1. For $\xi > 4.66$ condition (22) is stronger than (17).

Concluding Remarks

It is of interest to compare conditions (15), (17), and (22) to the stability condition for the case of a constant follower force. If $p(t) = p_0 = \text{constant}$ and $\xi = 0$, Beck [3] showed that the column is stable if and only if

$$p_0 < 2.008\pi^2. \quad (24)$$

For $\xi > 0$ (24) is a sufficient condition for asymptotic stability [4]; it is also a necessary condition if ξ is small enough.

In conclusion, we point out that the stability regions derived here and shown in Fig. 1 surely comprise only a part of the total stability region. However it is believed that these results represent the first stability criteria obtained for a cantilevered column subjected to a time-dependent follower force.

Acknowledgments

The author wishes to thank Professor E. F. Infante of Brown University and Professor C.S. Hsu of the University of California for many helpful discussions and suggestions.

References

- [1] Infante, E. F., "On the Stability of Some Linear Nonautonomous Random Systems", Journal of Applied Mechanics, Vol. 35, No. 1, Trans. ASME, Vol. 90, Series E, March 1968, pp. 7-12.
- [2] Caughey, T. K., and Gray, A. H., Jr., "On the Almost Sure Stability of Linear Dynamic Systems With Stochastic Coefficients", Journal of Applied Mechanics, Vol. 32, No. 2, Trans. ASME, Vol. 87, Series E, June 1965, pp. 365-372.
- [3] Beck, M., "Die Knicklast des einseitig eingespannten, tangential gedrückten Stabes", Zeitschrift für angewandte Mathematik und Physik, Vol. 3, 1952, pp. 225-228 and 476-477 (errata).
- [4] Leipholz, H., "Über den Einfluss der Dämpfung bei nichtkonservativen Stabilitätsproblemen elastischer Stäbe, "Ingenieur-Archiv, Vol. 33, 1964, pp. 308-321.

Fig. 1 Stability Conditions

